

PRESSURE RELEASE VALVE - DA

- Can Withstand Pressures upto 8Kg/sq.cm
- Economical
- Wide Pressure Range
- Sold separately as an accessories



SPECIFICATIONS

- 1) Direct Acting – Spring loaded Pressure Release Valve
- 2) Designed Pressure: Upto 10Kg/Sq.cm
- 3) Working Setting Pressure: 1.5 to 8Kg/Sq.cm

APPLICATIONS

- 1) PRV-DA is widely used in the irrigation system
- 2) Used as a safety valve
- 3) Designed to protect pressurized system
- 4) Can be installed near motor/pump to relieve sudden back pressure

THREAD CONNECTIONS

- 1) Inlet Thread: 2" BSP Female Thread
- 2) Outlet Thread: 1 ½" BSP Female Thread

MATERIALS CONSTRUCTION

- 1) Virgin Engineering Polymer
- 3) Seal: High Performance Rubber
- 4) Spring: Stainless Steel
- 5) Bolts: Stainless Steel
- 6) Weather Resistant

GENERAL INSTALLATION GUIDELINES

- 1) Install PRV-DA as per the flow direction arrow
- 2) The valve can be installed at any angle



Jain's Mobile App

Note: Sold separately as an accessories



Tel: +91-257-2258011; **Fax:** +91-257-2258111; **E-mail:** jisl@jains.com; **Website:** www.jains.com
Toll Free: 1800 599 5000

