

Filt-O-Clean


Automatic Filter Backwash Controller



Features & Benefits



Assembled in high quality thermoplastics box with IP55 protection and transparent lid



One touch key pad for easy programming



Bicolour LED, turns red while flushing cycle is on and can be easily seen through transparent lid



Flexibility in input power supply, either on 230 VAC or 12 VDC.

Features

- 16 char x 2 line user friendly and self-explanatory LCD screen.
- Flush time can be set from 0 to 59 minutes in one minute increments.
- Wait interval can be set from 1 minute to 23 hrs & 59 minutes.
- Count down timer shows status of backflush.
- Pause option, can be paused during operation. Useful to pause backwash during fertigation
- Output 12 VDC (pulse). 24 VAC model can be supplied on demand.
- Can be supplied with solar power option on demand
- Manual override facility
- Available in 1, 2, 3, 4, 5 & 6 station models. Higher models can be supplied on demand

- Inbuilt SMPS for spike suppression and compensation for frequent supply variations
- Facility to operate on pressure differential mode. Inbuilt melody tune to alarm the user for manual intervention, if pressure difference is not reduced to set point after two attempts by the controller
- Spacious wiring compartment

Application

- For controlling automatic periodical backwash operation of media filters

Ordering Specifications

SKFFBWDC

Note: Solar kit for filter backwash controller. Consists of 10 Watt panel, 12 V battery with case, charge controller and 1 mtr. Two core wire for connections.